

REDEFINING THE BOUNDARIES OF THERMAL INKJET TECHNOLOGY



Z20 REACH THE NEXT GENERATION OF ZAUQ PRINTERS

- ⚙️ Touch screen controller
- ⚙️ Dual printhead support
- ⚙️ Message length up to 2m
- ⚙️ Printing speed up to 40m/min at 300dpi
- ⚙️ Throw distance up to 10mm
- ⚙️ Universal UI software
- ⚙️ Data cable standard 2m


MEK-BASED INKS

zauq
GROUP
INNOVATE • TRANSFORM • INSPIRE
WWW.ZAUQ.COM

 **Thermal
Ink Jet**

 **HEAD OFFICE**
16 Johar Town Lahore Pakistan.
Tel: +92 42 35314777, 35314888
Tel: +92 32 11 22 38 88
Email: info@thermalinkjet.com
Website: www.thermalinkjet.com

 **KARACHI OFFICE**
246-D, KDA Scheme 1,
Karachi, Pakistan.
Tel: +92 32 11 22 39 99
Email: info@thermalinkjet.com
Website: www.thermalinkjet.com

 **ISLAMABAD OFFICE**
Ground Floor,
National Science & Technology
Park H-12, Islamabad, Pakistan
Tel: +92 32 11 22 37 77
Email: info@thermalinkjet.com
Website: www.thermalinkjet.com

Z20 REACH

TECHNICAL SPECIFICATIONS

Printing Technologies	Thermal Inkjet Technology from Funai, Japan
Dimensions (LxWxH)	Controller (193 x 130.3 x 34.5 mm) 0.5 inch printhead (210.4 x 60.8 x 74.15 mm)
Weight	Controller (888 grams), Printhead max (540 grams)
Display	Touch screen 7 inches
Power Supply	AC 100V-240V, 50/60Hz, DC 24V 2.5A, Maximum power consumption: 60W
Resolutions	Max 300x600dpi
Print speed	Max 29m/min @ 300x300dpi - 40m/min @ 300x200dpi
Density	Up to 3 levels of optical density
Throw Distance	Up to 10mm

FEATURES

Printability	Text, Counter, Box/Lot, Datetime, Expiry Date, Julian Date, Shiftcode, Image, Database (TXT, CSV, SQL, MySQL, SQLite, JSON) Barcodes (Code 11, Code 39, Code 128, EAN, QR, Datamatrix, GS1 Datamatrix...) POD (Print online data)
Advance	Free design in template up to 1 inch (2 heads) Integrate with other devices (PLC, Camera, Checkweigher...) via RJ45 Real-time Printing WYSIWYG (what you see is what you get) Data upload, Backup & Recovery via USB
External connection	Build in sensor External Sensor, Encoder and Alarm beacon
Length Template	Maximum length of template up to 2m
Menu languages	English (default), German, Vietnamese, Chinese, Korean, Russian, Turkish, Portuguese, Spanish, Polish, Greek and Italian
Memory	Store up to 8GB template on the printer's memory
Printable characters	Windows true fonts Automatic recognition ink type and ink parameters
Ink Management	Nozzle warming, auto-jet and self-cleaning capabilities to extend cartridge lifetime Nozzle status checking
Ink Solutions	Solvent ink for porous and non porous material Aqueous ink for printing on porous and semi porous material Support ink color: ●
Operating condition	Temperature 5 - 50°C and 90% air humidity, non-condensing

